



## Tagalong 6 Ton Series

|  |  |
|--|--|
| • G.V.W.R. - 12,000 #                                | • Axles - 2 Dexter 6,000 # single wheel electric brake axles |
| • G.A.W.R. (Each Axle) -6,000 #                      | • Suspension-Multi-leaf slipper spring w/equalizer           |
| • Coupler - 3 position adjustable                    | • Tires - ST 235/80R 16" Load Range D                        |
| • Safety Chain - 3/8" grade 43 with hooks            | • Wheel - 6.75 x 16" 8 bolt white spoke                      |
| • Jack - 10,000 # drop leg                           | • Deck - 2" pressure treated pine                            |
| • Frame - 8" channel                                 | • Lights - D.O.T. stop, tail, turn, and clearance            |
| • Crossmembers - 3" channel on 16" center            | • Elec. Plug - 7-way RV                                      |
| • Side rails - 6" channel w/stake pockets /rub rails | • Paint - High solids acrylic enamel                         |

### Standard Features

### Optional Features

|                                 |                           |
|---------------------------------|---------------------------|
| • Crossmembers on 16" centers   | • Dual jacks              |
| • Sealed modular wiring harness | • Steel deck              |
| • Electric breakaway            | • D-Rings                 |
| • E-Z Lube axles                | • Electric over hydraulic |
| • 5' Dovetail                   | • Pop up dovetail         |
| • 5' Ramps                      |                           |
| • Tool tray in tongue           |                           |

### Dimensions

| Length | A    | B       | C   | D   | E   |
|--------|------|---------|-----|-----|-----|
| 25'    | 300" | 178.75" | 68" | 37" | 96" |
| 29'    | 348" | 202.75" | 68" | 37" | 96" |

